



# MULTISPLIT INDOOR UNITS

Medium static pressure ducted

HUCU 351-531 ZAL



Wired remote control included

Compatible with systems **AIRZONE**

Condensate drain pump included with possibility of raising the discharge up to 750 mm from the lower height

Model	HUCU 351 ZAL		HUCU 531 ZAL
Type	Indoor ducted unit		
Control (included)	Wired remote		
Rated capacity	Cooling	kW	3.50
	Heating	kW	3.80
<b>Electrical data</b>			
Power supply	Ph-V-Hz	-	
Connection wires between I.U. and O.U.	no.	4	
<b>Refrigerant circuit</b>			
Diameter of refrigerant piping on liquid/gas	mm (inches)	ø6.35(1/4") - ø9.52(3/8")	
<b>Product specifications</b>			
Dimensions	LxDxH	mm	700x506x200
	Net weight	Kg	17.8
Sound pressure level	Hi/Mi/Lo/U/Lo	dB(A)	34.5/30.5/29/23
Sound power level	Hi	dB(A)	57
Treated air (Hi/Me/Lo)		m³/h	600/480/300
Fan static pressure	Std/Max	Pa	25/60
Motor power (Output)		W	130
<b>Optional parts</b>			
Wired remote control			YES
Centralized control			YES

# MULTISPLIT INDOOR UNITS

Ceiling HSFU 531 ZAL



Remote control included as standard

Excellent installation flexibility

Turbo function, for heating and cooling rooms quickly

Model	HSFU 531 ZAL		
Type	Indoor ceiling unit		
Control (included)	Remote control		
Rated capacity	Cooling	kW	5.30
	Heating	kW	5.60
<b>Electrical data</b>			
Power supply	Ph-V-Hz	-	
Connection wires between I.U. and O.U.	no.	4	
<b>Refrigerant circuit</b>			
Diameter of refrigerant piping on liquid/gas	mm (inches)	ø6.35(1/4") - ø12.74(1/2")	
<b>Product specifications</b>			
Dimensions	LxDxH	mm	1068x675x235
	Net weight	Kg	28
Sound pressure level	Hi/Mi/Lo/U/Lo	dB(A)	43.5/41/36.5/24
Sound power level	Hi	dB(A)	57
Treated air (Hi/Me/Lo)		m³/h	958/839/723
Motor power (Output)		W	96
<b>Optional parts</b>			
Wired remote control			YES
Manual centralized control			YES
Wi-Fi centralized control			YES